



FRP

SPRAY ADHESIVE



For vertical and horizontal installation of EcoFoil products

PRODUCT CHARACTERISTICS

Spray-Lock FRP Spray Adhesive bonds approved EcoFoil products for commercial and residential applications. Material must be structurally sound for use in commercial or residential applications.

Spray-Lock FRP Spray Adhesive uses 60% less adhesive than traditional trowel-on adhesives.

Spray-Lock FRP Spray Adhesive increases productivity with a faster application rate, saving time and money. Spray-Lock FRP Spray Adhesive comes in an easy-to-use aerosol can.

ADVANTAGES

- Cuts labor cost by about 30%
- 8-hour working time
- Apply directly to wall/floor substrate or back of material for overhead/ceiling applications
- Releasable for repositioning (prior to rolling)
- Adheres to porous and non-porous substrates
- 0.0 g/mL VOC content
- Water-based adhesive
- Easy water cleanup while adhesive is still wet
- Non-flammable
- No offensive odors

*According to EPA document: "National Volatile Organic Compound Emission Standards For Consumer Products" for aerosol adhesives.

SUITABLE SUBSTRATES

Spray-Lock FRP Spray Adhesive adheres to most smooth, clean surfaces, including properly prepared:

- Plywood
- Drywall
- Water Resistant Drywall
- Approved Cement Board
- Metal
- FRP
- Ceramic Tile
- Concrete Substrates
- Block Wall

NOTE: Prime all joint compound.

TECHNICAL CHARACTERISTICS

Spray-Lock FRP Spray Adhesive is a water-based acrylic blend spray adhesive that has milky white frost bubbles in appearance and provides immediate shear strength after tack during installation.

Spray-Lock FRP Spray Adhesive is solvent free, emits no harmful fumes, and contains 0.0 g/mL VOC (Volatile Organic Compounds) in content, according to EPA Test Method 8260B.

Spray-Lock FRP Spray Adhesive uses non-ozone depleting HFC propellant.



www.spraylock.com
423.305.6151



www.ecofoil.com
888.349.3645

TECHNICAL DATA

CHEMICAL TYPE	Water-based acrylic blend
APPEARANCE	Milky white frost bubbles
ODOR	Sweet mild odor
FLASH POINT	Will not burn
NFPA 704 FLAMMABILITY RATING	0 (Non-flammable)
SHELF LIFE	3 years, if unopened
OPEN TIME	8 hours
DRY TIME	Once adhesive is dry to touch (10-20 minutes)
VOC CONTENT	0.0 g/mL calculated per EPA Test Method 8260B
STORAGE	Do not subject to freezing temperatures
CLIMATE-CONTROL SETTINGS	Building owners should become aware of the wall and flooring material manufacturer's guidelines for climate-control settings (temperature and humidity). These conditions must be monitored and kept constant to ensure the overall performance and long-term success of the installation.



COVERAGE GUIDE

FRP ADHESIVE | 22 oz AEROSOL CAN

100 ft² (3.9 m²)

Coverage rates are a guide and figures will increase or decrease depending on the spraying technique implemented. Please refer to the Install Guide for detailed instructions.

DATE: 05.08.23
REV: REL